



# AR/FR DUAL CERTIFIED INSULATED JACKET & BIB OVERALL

### PRODUCT INFORMATION









**UL Certified NFPA 2112** NFPA 70E, ASTM F1506 385-FRBO AR/FR DUAL CERTIFIED INSULATED BIB OVERALL in the cold. The PIP® FR garments are engineered with high-performance materials to provide advanced thermal protection, flame resistance and protection against arc flash exposure.

#### **Ideal For**

- Mining Crews
- Petrochemical
- Oil & Gas Workers
- Utilities
- Welding



# ENGINEERED TO PROVIDE ADVANCED THERMAL PROTECTION, FLAME RESISTANCE AND PROTECTION AGAINST ARC FLASH EXPOSURE





Outer Shell

Zip-In Liner

# PIP® 4-in-1 Dual Certified Ripstop Jacket With Zip-Out Insulated Liner

#### 385-FRFC

S-5XL

#### Outer Shell:

- > 7oz FR ripstop 88% cotton, 12% nylon fabric with 7oz khaki FR twill weave fabric for lining
- > High tenacity Aramid FR thread, bar-tacked at all stress points
- > Protective stand-up collar with hook and loop closure
- > Detachable hood with 3 snaps that attach to jacket
- > Heavy duty brass zipper, with storm guard and hook and loop closure
- > Adjustable hook and loop sleeve tab
- > Renewably sourced, non-fluorinated water repellent treatment
- > ATPV 26 cal/cm², PPE CAT 3

#### Zip-In Liner:

- > 7oz FR ripstop 88% cotton, 12% nylon fabric with 14oz khaki 100% Modacrylic lining
- > High tenacity Aramid FR thread, bar-tacked at all stress points
- > One-way reversible resin zipper on Aramid tape
- > Can be worn alone or zipped into outer shell
- > Detachable sleeves to covert into vest
- > Renewably sourced, non-fluorinated water repellent treatment
- > ATPV 33 cal/cm², PPE CAT 3



#### PIP® Dual Certified Ripstop Bib Overall

#### 385-FRBO

S-5XL

- > 7oz FR ripstop 88% cotton, 12% nylon fabric with 7oz khaki FR twill weave fabric for lining
- > 14oz 100% modacrylic insulation
- > Two-way heavy-duty brass zipper on Aramid tape at center front
- > Elasticized shoulder strap with adjustable buckles
- > 28-inch xipper at leg with storm guard and snap closure
- > Renewably sourced, non-fluorinated water repellent treatment
- > ATPV 33 cal/cm², PPE CAT 3

## 4 CONFIGURATION OPTIONS FOR JACKET









