

Standard Butyl Glove

Style # IUB0025/R, IUB0014/R, and IUB0007/R

ISO 9001:2000

Registered

CHEMICAL PROTECTIVE GLOVES

The Standard Butyl

Our basic model that protects against a wide range of chemicals. Available in three thicknesses to meet your specific needs for protection and dexterity. Curved-hand design for comfortable use.

Length 14"
 Sizes x-sm., sm., med., lg., x-lg
 Thicknesses . . . light, medium, heavy
 Finishes smooth or rough-grip
 Design straight-hand

CHEMICAL	Break Through time (min.)	Permeation rate (ug/cm ² -min.)	CHEMICAL	Break Through time (min.)	Permeation rate (ug/cm ² -min.)
1, 1, 1 Trichloroethane	NT	NT	Gasoline	NT	NT
1, 3 Butadiene	303	0.3	N-Hexane	4	>500
Acetaldehyde	4	2.1	Hydrochloric Acid (37%)	ND	NA
Acetic Acid (glacial)	ND	NA	Hydrofluoric Acid (49%)	ND	NA
Acetone	ND	NA	Hydrogen Chloride	ND	NA
Acetonitrile	ND	NA	Hydrogen Fluoride (99%)	15	>100
Ammonia	ND	NA	Methyl Alcohol	ND	NA
Ammonium Hydroxide	ND	NA	Methyl Chloride	176	0.9
Ammonium Nitrate	ND	NA	Methyl Ethyl Ketone (MEK) 99%	376	1.1
Aniline	ND	NA	Methyl Isobutyl Ketone (MIBK) 99.5%	340	1.1
Benzene	NT	NT	Methylene Chloride	20	>500
Butyl Acetate	94	10	Methylchloroform	NT	NT
p-tert-Butyl Toluene	91	>32	Muriatic Acid	ND	NA
Carbinol	ND	NA	N-ethylethanamine	27	>500
Carbon Disulfide	<4	>500	Nitric Acid (conc.)	ND	NA
Chlorine	60	>50	Nitric Acid (red fuming)	NT	NT
Chloromethane	176	0.9	Nitrobenzene	ND	NA
Chloroethene	NT	NT	Nitropropane	ND	NA
Cyclohexane	4	>23	Oleum	270	>500
Cyclohexanol	ND	NA	Pentachlorophenol	NT	NT
Cyclohexanone	ND	NA	Pentane	NT	NT
Dibutyl Phthlate	ND	NA	Phenol	NT	NT
Diethylamine	27	>500	Phenylamine	ND	NA
Dimethylacetamide (DMAC)	480	NA	Phosphoric Acid	ND	NA
Dimethylformamide (DMF)	ND	NA	Potassium Hydroxide	ND	NA
Dioxane	ND	NA	Propyl Acetate	109	19
Divinyl Benzene	54	>64	Sodium Hydroxide	ND	NA
Ethanal	4	2.1	Sulfuric Acid	ND	NA
Ethanamine	ND	NA	Sulfuric Acid (fuming)	270	>500
Ethyl Acetate	253	>500	Tetrachloroethylene	<4	>500
Ethyl Alcohol	ND	NA	Tetrahydrofuran	25	>500
Ethyl Aldehyde	4	2.1	Toluene	28	>500
Ethyl Benzene	NT	NT	Toluene Diisocyanate	NT	NT
Ethylamine	ND	NA	Xylene	NT	NT
Ethylene Oxide	173	3.53	Vinylethylene	75	NA
Flouhydric Acid	ND	NA			

Tests performed on IUB0025R (heavy weight) except as indicated. All tests above performed per ASTM F739 by TRI/Environmental, Inc. at ambient temperature for 8 hours. Tests were performed under laboratory conditions and do not represent actual usage conditions. TRI/Environmental makes no warranties or other guarantees concerning protection by these materials and assumes no liability for use of this material with the chemicals tested.

The user should determine the applicability of conditions when assessing suitability of the actual anticipated exposures.

The breakthrough times and permeation rates reported are the average of three test replicates. ND = no breakthrough in 8 hours; NA = not applicable; NT = not tested. Minimum detection limit (ppm), 1.0 or less (except when that is not possible).

CHEMICAL	1UB0025/R BUTYL HVY. WT.		1UB0014/R BUTYL MED. WT.		1UB0007/R BUTYL LT. WT.	
	b/t	rate	b/t	rate	b/t	rate
methylisobutyl ketone MIBK 99.5%	340	1.3	NT	N/A	68	7.6
methyl ethyl ketone (MEK)	376	1.1	116	55	NT	N/A

LIGHT WEIGHT = 7 mil thickness MEDIUM WEIGHT = 14 mil thickness
 HEAVY WEIGHT = 25 mil thickness