



# SPECIFICATION SHEET

## 148-5000

### TOP GRAIN GOATSKIN LEATHER PROTECTOR FOR NOVAX® GLOVES – GAUNTLET CUFF

- Top grain goatskin leather construction is the softest, most abrasion-resistant leather and is highly recommended for applications requiring tactile sensitivity
- Top grain leather is smooth, provides durability and dexterity
- Split leather gauntlet cuff for added forearm protection and allows for fast removal
- Straight thumb increases comfort in closed-fisted work
- Nylon strap with buckle for a secure, personal fit
- Cotton color binding denotes sizing
- Meets ASTM F696-06 (2011) standard

### APPLICATIONS

- For use with Class 1-2 rubber insulating Novax® gloves. Cover glove to be used only for mechanical protection for rubber insulating gloves. Not to be used for electrical protection per ASTM F696-06 - 2011.

### TECHNICAL DATA

MATERIAL	100% Goatskin Leather				
COLOR	■ Natural				
CUFF STYLE	Gauntlet				
SIZES	8 - 12				
PACKAGING	12 per dozen, 24 pair per case				
CASE DIMENSIONS	8: 15.7" x 9.8" x 10.6" / 40cm x 25cm x 27cm 9: 16.5" x 9.8" x 10.6" / 42cm x 25cm x 27cm 10: 16.9" x 10.6" x 11" / 43cm x 27cm x 28cm 11&12: 17.1" x 10.6" x 11" / 43.5cm x 27cm x 28cm				
CASE WEIGHT	8	9	10	11	12
	14.3 lbs 6.5 kg	15.4 lbs 7.0 kg	16.5 lbs 7.5 kg	17.6 lbs 8.0 kg	18.7 lbs 8.5 kg
COO	China				



### DIMENSIONS (in/cm)

	8	9	10	11	12
<b>A</b>	10.5 / 26.7	11.5 / 29.2	11.8 / 29.9	12.0 / 30	12.0 / 30
<b>B</b>	4.9 / 12.4	5.1 / 13.0	5.4 / 13.7	5.8 / 14.8	6.0 / 15.2
<b>C</b>	3.1 / 7.8	3.1 / 7.8	3.1 / 7.8	3.1 / 7.8	3.1 / 7.8
<b>H</b>	■ Red	■ Green	■ Brown	■ Blue	■ Black

Leather Thickness: 0.8mm / Cuff Thickness: 1.6mm

### MAX USE VOLTAGE

CLASS	AC VOLTS	DC VOLTS
1 - 2	7,500 - 17,000	11,250 - 25,5000

**10** NOVAX™ by G.B. INDUSTRIES  
ANSI / ASTM CLASS 1 TYPE I  
MAX USE VOLT 7500V AC

**10** NOVAX™ by G.B. INDUSTRIES  
ANSI / ASTM CLASS 2 TYPE I  
MAX USE VOLT 17000V AC

### BARCODES

ITEM	BAG	DOZEN	CASE
■ 148-5000/8	---	01616314063571	02616314063570
■ 148-5000/9	---	01616314063588	02616314063587
■ 148-5000/10	---	01616314063595	02616314063594
■ 148-5000/11	---	01616314063601	02616314063600
■ 148-5000/12	---	01616314063618	02616314063617

