



SPECIFICATION SHEET

16-564



G-TEK® POLYKOR® INDUSTRY GRADE SEAMLESS KNIT BLENDED GLOVE WITH POLYURETHANE COATED SMOOTH GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor® shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

TECHNICAL DATA

MATERIAL	PolyKor® Fiber / Polyurethane						
CONSTRUCTION	Seamless Knit						
GAUGE	13						
COLOR	■ Gray						
CUFF STYLE	Knit Wrist						
SIZES	XXS - XXL						
PACKAGING	12 pair per dozen pack; 6 dozen per case						
CASE	14.2" x 11.8" x 12.6" / 38cm x 30cm x 25cm						
CASE WEIGHT (lbs / kg)	XXS	XS	S	M	L	XL	XXL
	9.7 / 4.4	10.3 / 4.7	11.02 / 5	11.6 / 5.3	12.3 / 5.6	13.6 / 6.2	14.5 / 6.6
COO	China						




BARCODES

ITEM	PAIR	DOZEN	CASE
■ 16-564/XXS	---	10616314294010	20616314294017
■ 16-564/XS	---	01616314272140	02616314272149
■ 16-564/S	---	01616314259127	02616314259126
■ 16-564/M	---	01616314259134	02616314259133
■ 16-564/L	---	01616314259141	02616314259140
■ 16-564/XL	---	01616314259158	02616314259157
■ 16-564/XXL	---	01616314259165	02616314259164

DIMENSIONS (in/cm)

	XXS	XS	S	M	L	XL	XXL
A	8.4 / 21.5	8.9 / 22.7	9.2 / 23.5	9.3 / 24.5	9.6 / 25.5	10 / 26.5	10.8 / 27.5
B	3.4 / 8.8	3.5 / 9	3.7 / 9.5	3.9 / 10	4.1 / 10.5	4.2 / 10.8	4.4 / 11.2
H	□ White	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Sky Blue



PERFORMANCE PROPERTIES

EN388: 4X4D	ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	5
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT (TDM-100)	A	B	C	D	E	F

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.