

SPECIFICATION SHEET 280-CW4200

PIP™ 4200 SERIES CAP STYLE HARD HAT WITH WHEEL RATCHET

- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) minimizes fatigue
- 4-Point suspension with HDPE strap and webbing clips provide a comfortable and secure fit
- Revolution[™] Wheel Ratchet is easy to use and creates a firm comfortable fit
- Unique "3D Adjustment" provides a precise fit using harness depth settings
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when you're looking down or bending over
- Chamlon[™] sweatband made with an Egyptian cotton core and porous PU coating for maximum sweat absorption, pH neutral and dermatologically tested
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Meets ANSI/ISEA Z89.1
- Fulfills Class E Electrical Insulation requirements
- Not compatible with the JSP[®] EVOSpec[™] or CR2 reflective kits
- · Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- · High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating					
COLOR	□ White (-10) ■ Green (-30) ■ Red (-60) ■ Yellow (-20) ■ Blue (-50) ■ Bright Orange (-0R)					
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")					
EACH WEIGHT	12.6 oz					
PACKAGING	10 per case					
CASE	23 5/8" x 9 1/2" x 16 1/8" / 60cm x 24.13cm x 40.95cm					
CASE WEIGHT	9 lbs / 4.1 kg					
C00	USA					




BARCODES

ITEM	EACH	DOZEN	CASE
280-CW4200-10	848309014584		20848309014588
280-CW4200-20	848309014591		20848309014595
280-CW4200-30	848309014614		20848309014618
280-CW4200-50	848309014621		20848309014625
280-CW4200-60	848309014638		20848309014632
280-CW4200-OR	848309014645		20848309014649

DIMENSIONS (in)

	OSFA			
Α	11 5/16			
В	6			



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products. Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.