



# SPECIFICATION SHEET

## 390-EZ100

### EZ® COOL FLASH EVAPORATIVE COOLING VEST

- Lightweight Easy to activate and durable
- 1-2 Minute activation time
- Can provide 5-10 hours of cooling relief per activation
- Cools the body 15-20 degrees from the ambient temperature
- Provides uniform cooling affect without the swelling and slim affect
- Dries after use and when stored properly eliminates the chance of mold or mildew setting in
- Comfortable quilted nylon outer, inner cooling fabric with water repellant nylon liner
- V-neck design with zipper closure

### APPLICATIONS

- Roadway construction workers
- Mining
- Farming
- Emergency response personnel
- Industrial sites
- Sporting events

### CARE INSTRUCTIONS

Always store in clean, dry conditions. DO NOT store in places subject to direct, strong sunlight. Spot wash or hand wash ONLY.

### TECHNICAL DATA

|             |                                      |
|-------------|--------------------------------------|
| MATERIAL    | Polyester / Nylon                    |
| COLOR       | Hi-Vis Lime Yellow                   |
| SIZES       | S-3X                                 |
| PACKAGING   | 1/Polybag, 25/ Case                  |
| CASE        | 16" x 18" x 24" / 41cm x 46cm x 61cm |
| CASE WEIGHT | 34lbs / 15.4kg                       |
| COO         | China                                |

### BARCODES

| ITEM            | BAG          | DZ OR BOX      | CASE           |
|-----------------|--------------|----------------|----------------|
| 390-EZ100-LY/S  | 616314207051 | 01616314207050 | 02616314207059 |
| 390-EZ100-LY/M  | 616314207068 | 01616314207067 | 02616314207066 |
| 390-EZ100-LY/L  | 616314207075 | 01616314207074 | 02616314207073 |
| 390-EZ100-LY/XL | 616314207082 | 01616314207081 | 02616314207080 |
| 390-EZ100-LY/2X | 616314207099 | 01616314207098 | 02616314207097 |
| 390-EZ100-LY/3X | 616314207105 | 01616314207104 | 02616314207103 |



### DIMENSIONS (in/cm)

|          | S / M        | L / XL       | 2X / 3X      | 4X / 5X      |
|----------|--------------|--------------|--------------|--------------|
| <b>A</b> | 49.0 / 124.5 | 53.0 / 134.6 | 57.0 / 144.8 | 61.0 / 155.0 |
| <b>B</b> | 24.0 / 61.0  | 26.0 / 66.0  | 28.0 / 71.0  | 30.0 / 76.2  |

