

# SPECIFICATION SHEET R5T

## **PACIFIC R5T RESCUE HELMET**

- Certified to meet AS180T 1 & 2
- Compliant with ANSI Z89.1
- Lightweight Dupont™ Kevlar® composite shell weighs less than composite fiberglass and composite alternatives
- Shell is not affected by UV exposure
- $^{\bullet}$  Composite resins offer higher temperature resistance (up to  $600^{\circ}\text{F})$  without distorting or melting
- Ratchet headband with easy-to-adjust dial which accommodates a variety of head sizes (52-64cm)
- Scallop-sided shell designed to accommodate a variety of earmuffs
- 3-point polyester chin strap with quick-release buckle keeps helmet in place for rescue applications
- Built in torch pod (torch sold separately) for use with 933-A104120 eLED torch
- Optional face shield protects against hazards & blood borne pathogens
- Neck protector (optional) for ear and neck protection
- ESS mounts make goggle attachment quick and easy, even with gloves on
- Full range of tailored Decals/Badges/Reflectorising available
- Ear muff mounting clips (optional) for secure fastening to helmet

## **APPLICATIONS**

- Rope rescue
- High angle
- Cave rescue

# **TECHNICAL DATA**

MATERIAL	Outer Shell: Kevlar® composite / Inner Shell: Polyurethane			
SUSPENSION	Pacific ribbon cradle			
COLOR	■ Blue (860-6032) ■ Daisy (860-6031) ■ Red (860-6030) □ White (860-6033)			
SIZES	OSFA, Adjustable			
PACKAGING	17 per case			
CASE	26.5" x 23.5" x 13" / 67.3cm x 59.7cm x 33.0cm			
CASE WEIGHT	21.25 lbs / 9.64			
C00	New Zealand			
HARM CODE	6505.10.6075			

## **WARRANTY**

6-year limited warranty

Each helmet also carries a 2-year limited warranty on impact liners and ratchet suspensions. Internal parts including crown pads, ribbons and sweatbands are NOT covered by this warranty.

## **BARCODES**

ITEM	EACH	DOZEN	CASE
860-6032	616314148972		02616314148970
860-6031	616314149009		02616314149007
860-6030	616314149146		02616314149144
□ 860-6033	616314149184		02616314149182



## **DIMENSIONS** (in/cm)

	OSFA		
A	11.4 / 29.0		
В	8.3 / 22.1		
С	6.8 / 17.3		

