



ESD

### Technical Data

Color	White
Sizes Available	XS-5XL
Packaging	Case
Packed	1/Case
Case Dimensions (cm)	61.00 x 40.60 x 30.50
Case Weight (kg)	35.30
Country of Origin	China
Construction	ESD Safe
Certifications	--
Product Circularity	Reusable / Launderable

### Performance Data

ISO Cleanroom	--
ANSI/ESD S20.20	--
Temperature Resistant	--
Static Control Property	--

### Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.

### Uniform Technology™

#### Disctek 5.0 Grid ISO 6 (Class 1,000) Cleanroom Frock

- Disctek 5.0 Fabric - 98% Polyester 2% Carbon
- Raglan sleeve
- Military collar
- Zipper at front opening
- Snaps at sleeve hems
- Grounding snaps at armpit, and midpoint of front and back sleeve seams
- Launder before wearing in an ISO cleanroom
- Meets standards required for use in ISO 6 (Class 1,000) - ISO 8 (Class 100,000) cleanrooms and other controlled environments

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-04-04