

SPECIFICATION SHEET

STYLE: 10-K46



Kut Gard®

FR Viscose / DuPont™ Kevlar® Blended Sleeve with Blue/Gold Elastic End and Thumb Hole

- 60% FR Viscose / 40% Kevlar blend
- Thermal and flame protection from heat and open flame of welding
- Offers cut resistance for light duty applications, 2-ply Kevlar cuff offers A3 cut resistance
- Exceptional comfort, lightweight, breathable, and shrink resistant
- Kevlar knit wrist offers cut and heat resistance and prevent debris from entering the sleeve
- Elastic end provides a snug fit and helps eliminate debris from entering the sleeve

Applications

- · Cut Resistance with Light Heat Protection
- **Automotive Applications**
- Glass Operations
- **Light Heat Applications**



Technical Data

Color	Brown
Sizes Available	Finished
Packaging	Bulk Pack
Packed	144/Case
Case Dimensions (cm)	50.80 x 45.70 x 10.40
Case Weight (kg)	11.79
Country of Origin	United States
Liner Material	FR Viscose, Kevlar
Top of Arm	Blue/Gold Elastic
Finger & Thumb	Thumb Hole
Ply	
Lining	
Construction	Cut-and-Sewn
Certifications	TAA Compliant
Product Circularity	Reusable / Launderable Recycled via Terracycle

Performance Data

Cut Level	A1
ANSI Puncture Level	
ANSI Contact Heat Level	1
ASTM F1358 Vertical Flame Level	1

Care Instructions









