



4X42FX

### Technical Data

|                      |   |
|----------------------|---|
| Color                | Black   |
| Sizes Available      | XS-XXL  |
| Packaging            | Bulk Pack   |
| Packed               | 6/Case  |
| Case Dimensions (cm) | 31.00 x 29.00 x 38.00                             |
| Case Weight (kg)     | 4.50  |
| Country of Origin    | China   |
| Liner Material       | PolyKor X7  |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers                                    |
| Grip                 | MicroSurface                                      |
| Gauge                | 18  |
| Cuff                 | Elastic   |
| Impact Protection    | --  |
| Construction         | Seamless Knit, Touchscreen Compatible             |
| Certifications       | Silicone Free                                     |
| Product Circularity  | Recycled via Terracycle<br>Reusable / Launderable |

### G-Tek® PolyKor® X7™

Seamless Knit PolyKor® X7™ Blended Glove with Nitrile Coated MicroSurface Grip on Palm & Fingers - Touchscreen Compatible

- Seamless construction offers increased comfort and breathability
- PolyKor™ blended shell with X7™ technology is super light-weight and thin, offering exceptional cut resistance and durability in a thin liner configuration
- MicroSurface Nitrile coated palm and fingertips provide a superior grip in dry, wet and oily conditions by reacting like tiny suction cups that attach themselves firmly to the material being handled
- Reinforced thumb croch for extended glove life, enhanced comfort, increased abrasion resistance and added durability in a high-wear area
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove

### Performance Data

|                                 |        |
|---------------------------------|--------|
| Cut Level                       | A7     |
| ANSI Abrasion Level             | 4      |
| ANSI Puncture Level             | 3      |
| ANSI Impact Level               | --     |
| ANSI Contact Heat Level         | --     |
| EN 388                          | 4X42FX |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

### Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-04