

SPECIFICATION SHEET STYLE: 385MFRCS



Bisley®

AR/FR Ripstop Industrial Taped Cargo Pant -Industrial Wash Durable

- ARC Rating: PPE 2 ATPV 9.0 cal/cm2
- Lightweight, 6oz FR inherent ripstop fabric for added durability
- High tenacity Aramid thread to withstand stress during fire exposure and high temperatures
- 2% Antistatic to help inhibit electrostatic discharge (ESD)
- 2 in silver FR reflective tape located below knees for optimal visibility
- Button at front waistband, with curved design to prevent gaping at back
- Two cargo pockets on side legs, two rear hip pockets, two front pockets
- Wide belt loops for added convenience
- Melamine FR buttons, and FR closures
- Dual-certified to NFPA 70E (ASTM F1506) and NFPA 2112-2023 standards
- OEKO-TEX® Standard 100



Technical Data

Color	Navy
Sizes Available	3030-5032
Packaging	Bagged Each
Packed	10/Case
Case Dimensions (cm)	56.00 x 38.00 x 24.00
Case Weight (kg)	15.00
Country of Origin	China
Fabric	Aramid Blend, Cotton, Modacrylic, Ripstop
Weight	
Weight Closure	 Buttons
· ·	Buttons
Closure	
Closure Total Pockets	6 Rear Hip Pocket, Slash Pocket,
Closure Total Pockets Pocket Type	6 Rear Hip Pocket, Slash Pocket, Waist Pocket

Performance Data

PPE Category	2
ANSI Type/Class	
CSA Class	
CSA Level	

Care Instructions



Only synthetic detergents should be used on this AR/FR garment. Do not use bleach, starch, fabric softeners or detergents containing hydrogen peroxide on this garment as they could negatively affect the protective properties.

