



PIP®

AR/FR Dual Certified Coverall with Vented Back - 9.2 Cal/cm2

- 7oz 90% Cotton 10% Nylon
- PPE2, ATPV 9.2 cal/cm2
- Aramid high tenacity FR thread
- No metal pieces on the garment
- Bar-tacked at all stress points
- Protective stand-up collar with velcro closure
- Storm guard with velcro closure
- Comfort vented back for breathability
- Action back for mobility
- Side elasticized waist
- FR rib knit cuffs
- Velcro on bottom
- 2 waist patch pockets with side access
- UL Certified
- NFPA 1975, NFPA 2112-2023
- NFPA 70E, ASTM F 1506
- CAN/CGSB 155.20-2000, CAN/CGSB 155.22-97
- OSHA 29 CFR1910.269
- EN ISO11611:2008, EN ISO11612:2008, EN ISO14116:2008

Applications

- Electrical Contractors
- Utility Work



Technical Data

Color	Tan
Sizes Available	S-5X
Packaging	Bagged Each
Packed	18/Case
Case Dimensions (cm)	56.00 x 41.00 x 41.00
Case Weight (kg)	23.00
Country of Origin	China
Clothing Type	Coveralls
Fabric	Cotton, Nylon
Weight	7oz
Hide	--
Closure	Hook and Loop
Construction	Vented Back
Certifications	OSHA 29 CFR 1910, NFPA 70E, UL Certified, ASTM F1506, NFPA 1975, NFPA 2112
Product Circularity	--

Performance Data

PPE Category	2
ARC Rating	9.2 cal/cm2
ANSI Type/Class	--

Care Instructions



Machine Wash



Water Temp 60°C



Do Not Bleach



Tumble Dry



Low Heat

Only synthetic detergents should be used on this AR/FR garment. Do not use bleach, starch, fabric softeners or detergents containing hydrogen peroxide on this garment as they could negatively affect the protective properties.