



# SPECIFICATION SHEET

STYLE: 205-420CV



## Technical Data

Color	Green
Sizes Available	S-5X
Packaging	Bagged Each
Packed	10/Case
Case Dimensions (cm)	60.00 x 38.00 x 23.00
Case Weight (kg)	24.00
Country of Origin	China
Fabric	Nylon, PVC
Thickness	0.42 mm
Hood	Attached
Length	--
Closure	Zipper
Construction	Double Storm Flap, Reinforced Wear Points
Certifications	ASTM D6413
Product Circularity	--

## Care Instructions



Do Not Wash

## ChemFR™

### Treated PVC Coverall with Hood - 0.42 mm

- Special PVC layered material provides protection against various liquid splashes and incidental contact
- High strength nylon for increased durability
- Seams are welded to enhance protection against chemical permeation
- Reinforced knees, elbows, and crotch provide added durability
- Oversized storm flap front for additional protection
- Treated to provide limited flammability and is self-extinguishing (ASTM D6413 test method)

## Applications

- Road Work
- Municipal
- Shipyards
- Railyard
- Agriculture
- Plant Maintenance
- Not designed for use in an ARC flash or flash fire application

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-02