

# SPECIFICATION SHEET

STYLE: 25DGT4



### Claw Cover®

Seamless Knit HPPE Steel/Spun Dyneema Sleeve with Elastic Cuff and Opening - 100% Silicone Free

- Raises the standards for performance knit sleeves offering an increase in overall performance and value compared to UHMPE sleeves
- Superior cut resistance, up to two times better compared with **UHMPE** sleeves
- Manufactured with Proprietary HPPE and Stainless Steel and also featuring Spun DSM Dyneema® with Polyster lining
- Superior abrasion and Fatigue Resistance, more than 3 times greater than traditional para-aramid sleeves for lower cost per use
- Exceptional comfort and fit
- Superior washability, can be washed repeatedly in Chlorine Bleach and caustic detergents to remove dirt, odor, grease, oil, and bacteria without degradation, shrinkage, or stiffening. Will retain its performance after multiple washings

## **Applications**

- High Tensile Strength, Extremely Flexible and Breathable
- **Industrial Applications**
- Food Processing



#### **Technical Data**

| Color                | Gray                         |
|----------------------|------------------------------|
| Sizes Available      | 18"                          |
| Packaging            | Bulk Pack                    |
| Packed               | 200/Case                     |
| Case Dimensions (cm) | 45.70 x 30.38 x 22.86        |
| Case Weight (kg)     | 10.09                        |
| Country of Origin    | United States                |
| Liner Material       | HPPE, Stainless Steel Wire,  |
|                      | Dyneema                      |
| Top of Arm           | Elastic Ends, Elastic Cuff   |
| Finger & Thumb       | Thumb Hole                   |
| Ply                  | Single-Ply                   |
| Lining               |                              |
| Construction         | Seamless Knit, Blousy        |
| Certifications       | Silicone Free, TAA Compliant |
| Product Circularity  | Reusable / Launderable       |
|                      | Recycled via Terracycle      |

#### Performance Data

| Cut Level                       | A5 |
|---------------------------------|----|
| ANSI Puncture Level             |    |
| ANSI Contact Heat Level         |    |
| ASTM F1358 Vertical Flame Level |    |

#### Care Instructions









