

SPECIFICATION SHEET

STYLE: 09-K1450



G-Tek® KEV™

Seamless Knit DuPont™ Kevlar® / Elastane Glove with Nitrile Coated Smooth Grip on Palm & Fingertips - Medium Weight

- Seamless knit construction provides comfort without sacrificing
- Kevlar® and Elastane fiber shell provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Nitrile smooth/flat coatings are highly impermeable to liquids, proving a very tacky dry grip for specific applications that require secure holding power
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Launderable for extended life and to reduce replacement costs

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



Technical Data

| Color | Yellow |
|----------------------|---|
| Sizes Available | XS-3XL |
| Packaging | Bulk Pack |
| Packed | 12/Case |
| Case Dimensions (cm) | 54.00 x 29.00 x 36.00 |
| Case Weight (kg) | 11.00 |
| Country of Origin | China |
| Liner Material | Kevlar |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Smooth |
| Gauge | 15 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | |
| Product Circularity | Recycled via Terracycle Reusable / Launderable |

Performance Data

| Cut Level | A2 |
|---------------------------------|--------|
| ANSI Abrasion Level | 4 |
| ANSI Puncture Level | 3 |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 3221BX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions









